



DVI-D	DVI-D	CABLE FUNCTION
PIN 1	PIN 1	TMDS DATA 2-
PIN 2	PIN 2	TMDS DATA 2+
PIN 3	PIN 3	TMDS DATA 2/4 SHILD
PIN 4	PIN 4	TMDS DATA 4-
PIN 5	PIN 5	TMDS DATA 4+
PIN 6	PIN 6	DDC CLOCK
PIN 7	PIN 7	DDC DATA
PIN 9	PIN 9	TMDS DATA 1-
PIN 10	PIN 10	TMDS DATE 1+
PIN 11	PIN 11	TMDS DATA 1/3 SHIELD
PIN 12	PIN 12	TMDS DATE 3-
PIN 13	PIN 13	TMDS DATA 3+
PIN 14	PIN 14	+5V POWER
PIN 15	PIN 15	GROUND(+5V)
PIN 16	PIN 16	HOT PLUG DETECT
PIN 17	PIN 17	TMDS DATA 0-
PIN 18	PIN 18	TMDS DATE 0+
PIN 19	PIN 19	TMDS DATE 0/5 SHIELD
PIN 20	PIN 20	TMDS DATA 5-
PIN 21	PIN 21	TMDSDATA 5+
PIN 22	PIN 22	TMDS CLOCK SHIELD
PIN 23	PIN 23	TMDS CLOCK+
PIN 24	PIN 24	TMDS CLOCK-
SHIELD	SHIELD	GROUND

ROHS

NOTES:

- 100% OPEN/SHORT TEST WITH 360 DEGREE SOLDERING.
- CONTACT RESISTANCE: 2Ω.
- INSULATION RESISTANCE: 50MΩ.
DC 500V AT 10ms.

NO.	DESCRIPTION	QTY	MATERIAL:	TOLERANCE	Unit:	Edt:	Title:	DWG No.:	Approved By:	Checked By:	Drawn By:	Date
6	CORE PVC MOLDING, BLACK 45P IN COLOR.			SELECT	mm	0	DVI-D 24+1					
5	CORE: 17.5*28.5*9.5.	2		ON. TOL. 1 2 3			Item: DVD-xxMM					
4	UL20276 7C*(1P*30#+D+AL)+1P*30#+3C*30#+AL+D+B, OD: 8.2, COLOR: BLACK IN COLOR.	1		0.000 +/- 0.05 0.1 0.15			Sample No:			JEFF.T		
3	THUMB SCREW: AF40*323TNPL35A BLACK IN COLOR.	4		0.0 +/- 0.15 0.3 0.5			Scale:			CRAIG.H		2005.03.23
2	ASS'Y PVC PLASTIC HOOD COLOR: BLACK IN COLOR OD8.5.	2		0. +/- 0.25 0.5 1.0			Tol:					
1	DVI-D 24PIN MALE CONNECTOR: G/F, INSULATOR BLACK, PLATED SHELL.	2		ANGLE +/-			Unit:					
								PCCABLES.COM Inc.				